



hot&cold

KIKKO MAX





Kikko Max is the free standing vending machine with a 620 cup capacity and up to 7 canisters which complements the Necta Hot & Cold range. With a height of 1830 mm, it has been designed to stand alongside the similarly sized Snakky Max or Sfera machines. The Kikko Max works in a master/slave mode and utilizes a single payment system which provides "One-Stop-Shopping" and creates an appealing machine bank, ensuring the most user friendly and practical vending service available.

ELECTRONIC CONTROL

The 16-bit electronic control with incorporated flash EPROM is extremely flexible and complete, as well as being compatible with the PC application GIGA. This allows a palmtop to be connected, via an RS232 interface, to allow the automatic set-up of the machine as well as the downloading of sales statistics and data (also in EVA-DTS format). With GIGA it is also possible to have remote monitoring of the machine using GSM technology.

PAYMENT SYSTEMS

Kikko Max is pre-set for the installation of systems with Executive, BDV and MDB protocol as well as for installation of validators.

At the same time, the following can be fitted:

- Change-giver, validator or coin mechanism
- Bill acceptor
- Cashless system with key or card.

ACCESSORIES

- Mechanical selections counter kit
- Lid for coin box kit
- Cup sensor + cup station lamp kit
- Cup station lamp kit
- 20 litre water tank kit
- 2x20 litre water tanks kit
- Still cooling unit kit (for powders)
- Master/slave kit
- RS232 jack kit
- GSM kit



Optimum internal access
Z 3000 patented coffee group

POWER CONSUMPTION	
Espresso version To reach operating temperature For each hour of stand-by	51.71 Wh 100 Wh
Instant version To reach operating temperature For each hour of stand-by	174.1 Wh 88.7 Wh

CAPACITY	
Cups (Ø 70-71 mm)	620*
Stirrers (length 95/105 mm)	550
Containers	6 ES / 7 IN
Espresso boiler	0.6 l
Instant boiler	2 l
Coffee beans	3.2 kg
Instant coffee	0.9 kg ES / 1.2 kg IN
Chocolate	5.2 kg
Milk	2.6 kg
Tea	3.2 kg
Sugar	4 kg
*166 cc	

CHARACTERISTICS	
Height	1830 mm*
Width	540 mm
Depth	650 mm
Overall depth with door open	1120 mm
Weight	126 kg ca.
Power supply voltage	230 V
Power supply frequency	50 Hz
Installed power	1800 W
Water mains pressure (With 3/4" gas male connection)	0.5 to 8.5 bar
*Adjustable feet: +10 -10 mm	



EXAMPLES OF POSSIBLE CONFIGURATIONS		
	KIKKO MAX ES 6 (Espresso Unit + 5 canisters)	KIKKO MAX IN 7 (7 canisters)
Pre-selections		
Sugar dosing	☞	☞
Bean coffee black	☞	
Bean coffee long	☞	
Bean café au lait	☞	
Bean coffee white	☞	
Instant espresso coffee		☞
Coffee long		☞
Café au lait		☞
Coffee white		☞
Cappuccino	☞	☞
Chocolate	☞	☞
Chocolate strong	☞	☞
Chocomilk	☞	☞
Decaf/Instant coffee black	☞	☞
Decaf/Instant coffee long	☞	☞
Decaf/Instant café au lait	☞	☞
Decaf/Instant cappuccino	☞	☞
Lemon tea	☞	☞
Soup		☞
Milk/Hot water	☞	☞
Cup only	☞	☞
No cup	☞	

L250U3

N&W Global Vending reserves the right to alter specifications without notice.

N&W GLOBAL VENDING S.p.A.

Via Roma, 24
24030 Valbrembo (BG) Italy
Tel. +39 035 606111 - Fax +39 035 606519



www.nwglobalvending.com